

CAT6A SCREENED PATCHCORD RJ45-RJ45



46-9628 CAT6A SCREENED PATCHCORD RJ45-RJ45-0.5m-Grey
46-9626 CAT6A SCREENED PATCHCORD RJ45-RJ45-0.5m-Blue
46-9638 CAT6A SCREENED PATCHCORD RJ45-RJ45-1m-Grey
46-9636 CAT6A SCREENED PATCHCORD RJ45-RJ45-1m-Blue
46-9648 CAT6A SCREENED PATCHCORD RJ45-RJ45-2m-Grey
46-9646 CAT6A SCREENED PATCHCORD RJ45-RJ45-2m-Blue
46-9658 CAT6A SCREENED PATCHCORD RJ45-RJ45-3m-
46-9668 CAT6A SCREENED PATCHCORD RJ45-RJ45-5m-Grey
46-9678 CAT6A SCREENED PATCHCORD RJ45-RJ45-10m-Grey

RJ45 patchcords, fully compliant to the Category 6A 600MHz standard using flexible S/FTP cable (individually foil-screened pairs plus overall screen) with a low smoke, zero halogen jacket. The connectors have gold plated contacts, metal body screen and flush strain-reliefs with 'snagless' cover, for high density patching.

LSZH: low Smoke Zero Halogen cable reduces the amount of toxic and corrosive gas emitted during a fire.

Supports 10 Gigabit Ethernet / 10GBASE-T: 10 Times faster than Gigabit Ethernet, 10GE (also called 10GbE or 10 GigE) supports a data rate of 10Gbits/s (billion bits per second).

S/FTP: Screened and Foil (Shielded) Twisted Pair. Each individual pair is screened by foil and features an overall outer sheath. This shielding protects the cable from EMI (Electro-Magnetic Interference).

Snagless Connectors: The connectors feature a “bubble” which protects the locking clip on the RJ45 from damage or being snapped off during transport or installation.

Flush Moulded Strain Relief: The flush moulded design allows the patch cables to be installed side by side in high-density network switches. The strain relief allows the cables to move without damaging the cable or breaking away from the connector while it is plugged in a device

This product has been tested and found to comply with the applicable electrical transmission characteristics specified in: ISO/IEC 11801 ED.2 and ANSI/TIA-568-C.2

IEC 60332-1-2, RoHS Compliant and 3P Verified

Product summary:

CAT6A 600MHz cable
4 pair x 26 AWG Copper conductors, Screened
Low Smoke Zero Halogen jacket
RJ45 Shielded connector with 50µ Inch Gold Plate
Injection moulded snagless connectors